

FlexFloor™ To Go With Padding Set Up and Dismantel Instructions

FlexFloor™ To Go With Padding Set Up and Dismantel Instructions

- The optimal use for Flex Floor would be on concrete/hard surface flooring. It is not recommended on carpet. If used on carpet, the Flex Floor will not stay in place or have a smooth look. Using the flooring on carpet could also cause potential damage to the Flex Floor.
 - Insure the ground is clear from any major debris like rocks, pieces of paper or any other object that may cause imperfections in the floor.
 - Remove flooring from case.
 - Lay out floor according to the diagram provided. Matching up the floor and pattern together will provide a more seamless appearance. Each piece will be numbered with arrows to indicate how the floor should be assembled.
 - Run the padding in the opposite direction. This will help in hiding seams. Use clear tape to secure the padding together at each seam.
 - It is not suggested to use any type of padding except for the recommended Ultra Step padding. Using any other type of padding (i.e. rebond) will not give an optimal performance, and could potentially damage the Flex Floor.
 - There are two ways to install the flooring with padding.
1. No finished edges – this is where the padding extends out to the edge of the floor. Tape the padding with double faced tape to the concrete/hard surface floor and then tape the Flex Floor to the padding.
 2. Finished edges: If you are using padding and desire a finished edge, the following may be completed to achieve this look. Using an exacto blade or sharp knife, cut 2-3 inches of pad from all outside perimeter edges. The width of a roll of double-faced tape can be used if you don't have a tape measure. Secure the edges of the Flex Floor down to the concrete to finish this tapered or feathered look.
- To improve the performance of the Flex Floor, tape the perimeter of the Flex Floor with clear tape or duct tape prior to applying the double faced tape. This will diminish the risk of tearing the Flex Floor backing. Please note that if the flooring is not installed for a permanent use but in a tradeshow application, warranties on this product will become void.
 - Use double faced tape around the perimeter of the Flex Floor to secure it to the substrate.
 - Floor is now ready to be used.
 - Dismantle: Be careful when pulling up Flex Floor. Try not to tear or stretch the flooring. Inform your installer that the floor should be removed from the ground slowly to minimize the possibility of damage.
 - Roll the flooring so that the pattern is facing to the outside of the roll. If you roll it with the backing towards the outside, you could potentially damage the floor.
 - Never fold the Flex Floor as this will damage the floor.
 - Place flooring inside its case and lock the lid down for safe storage.